

WHEELED WATER TANKS "CB-TR"

HOT GALVANIZED STEEL TUBULAR FRAME (powder coated for 300-400 L)

POLYETHYLENE TANK with ø 400 mm folding lid (except for 300/400L).

Wheel hubs adjustable in width. Steering angle of 180°.




15L hand wash tank – circuit washing tank (300-400 L excluded). Level indicator. **300-400 L**

External suction filter with valve, drain valve. **WITHOUT ACCESSORIES.**



AGRICULTURAL line

Wheeled Water Tanks 300 - 400 - 600 - 800 - 1000 - 1500 - 2000 - 3000 L

CODE	 Tank capacity	 Dimensions cm	 Weight
WITHOUT PUMP			
M2630015	300 L - POLYETHYLENE TANK	120x215x125	115
M2640015	400 L - POLYETHYLENE TANK	120x215x135	120
M2310600	600 L - POLYETHYLENE TANK	120x220x120	256
M2310800	800 L - POLYETHYLENE TANK	130x280x130	155
M2311000	1000 L - POLYETHYLENE TANK	130x280x140	326
M2311500	1500 L - POLYETHYLENE TANK	140x290x160	401
M2312000	2000 L - POLYETHYLENE TANK	150x310x160	465
M2313000	3000 L - POLYETHYLENE TANK	160x300x180	595







>> See below for pumps

>

ACCESSORIES

LAVCIRC20S	20 L CIRCUIT WASHING TANK (mandatory for professional use - ref. to EC2009/217 standard) for 300-400 L polyethylene models, for 600-1000 L fiberglass models
KITLUCI	REAR LIGHTS (for all versions)
KITOMOLOG	REAR BAR WITH LIGHTS AND SERIAL PLATE (for dry weight road homologation) (only for 1000-1500-2000 L in polyethylene CB-TR)
KITOMOLOG PC	Full load road approval (only for 1000L CB-TR)
KITGOM	TIRES AND XXL RIMS
MOZZ	HUBS FOR 150/200 CM TRACK WHEEL

PUMPS FOR TRAILED WATER TANKS COMPLETE WITH JOINT FOR PTO LINKAGE AND PRESSURE REGULATOR

 CODE	 Description	 L/min	 BAR	 Absorbed power HP	 Pressure Reg.
M301R	AR 30	32,0	40,0	2,9	GI 40
M406R	AR 403	40,0	40,0	3,7	GI 40
M501R	AR 503	55,0	40,0	5,6	RM 40
M630R	AR 813	80,0	50,0	8,8	RM 40
M32116R	AR 1064	105,0	50,0	13,1	VDR 50
M759R	AR 1203	120,0	50,0	13,6	VDR 50
M1200R	AR 70 bp (low pressure)	70,0	20,0	3,4	3 WAYS
M1203R	AR 115 bp (low pressure)	115,0	20,0	5,5	4 WAYS
M1206R	AR 135 bp (low pressure)	135,0	20,0	6,8	4 WAYS
M1209R	AR 160 bp (low pressure)	160,0	20,0	8,4	4 WAYS